



# GAM835



Dumper trailer, All Position



Dumper, All Position






Cement Mixer, All Position



Mixed Service

## Mixed Service All Position Tire



Features		Benefits
	Optimized tread width ratio	Uniform block stiffness delivers even wear and long mileage
	Three zigzag grooves with Y-style design	Increased traction with reduced stone retention
	Shoulder stepped groove design	Improved protection of casing, increased stability and comfort for the driver

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1494Q	16	H	148/145 K	8.25	7.50	6,940@123	6,395@123	11.0	19.3	41.5	24	501	133
315/80R22.5	100EV1182Q	22	M	161/157 J	9.00	9.75	10,200@131	9,090@131	12.3	19.7	42.4	24	490	156
11R24.5	100EV889Q	16	H	149/146 K	8.25	7.50	7,160@120	6,610@120	11.0	20.3	43.5	24	478	143

PR Ply Rating    LR Load Range    LI Load Index    SR Speed Rating    RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.

