







GDM635



Mixed Service Drive Tire

Features	Benefits
 <p>Strong independent block design</p>	Block layout optimization provides consistent traction
 <p>Ultra-wide tread and deep grooves</p>	Long service life in rugged conditions
 <p>Four steel-belt construction</p>	Exceptional durability and retreadability
 <p>Special cut/chip tread compound</p>	Provides excellent protection from tread cuts and chips in aggressive conditions

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1320Q	16	H	146/143 J	8.25	7.50	6,610@120	6,005@120	11.0	19.3	41.9	32	496	142
11R24.5	100EV884Q	16	H	149/146 J	8.25	7.50	7,160@120	6,610@120	11.0	20.5	43.9	32	473	152

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.

