

Features	Benefits						
Extra wide, deep tread pattern with special compound	Improved, longer tire life						
Three W-shaped pattern design	Improved traction performance and anti-wear properties						
Variable angle design	Improved stone ejection and water evacuation						
Enhanced casing construction	Provides improved footprint for excellent handling						

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	II Oaded	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	100EV1753Q	16	Н	148/145 J	8.25	7.50	6,940@123	6,395@123	11.0	19.3	41.5	24	501	136
275/70R22.5	100EV1520Q	16	Н	150/145 J (154/148 E)	8.25	9.00	7,390@130	6,395@130	10.9	17.5	37.7	24	551	125
295/80R22.5	100EV1793Q	18	J	154/150 J	9.00	8.25	8,270@123	7,390@123	11.7	19.2	41.3	24	503	153

PR Ply Rating
LR Load Range
SR Speed Rating
SLR Static Loaded Radius

