

	Features	Benefits
	New generation pattern with advanced groove design and extra-wide shoulder	Provides excellent shoulder area protection and even footprint for consistent wear
	New casing construction	Improved casing strength for exceptional durability and retreadability
	Specialized tread compound	Improved tread wear resistance and handling characteristics
M + S	Mud and Snow capabilities	Enhanced traction in mud and light snow for light duty applications

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs.@ PSI)	(Lbs.@ PSI)	Inch	Inch	Inch	32nds		Lbs.
215/75R17.5	100EV1451Q	16	Н	135/133 J	6.00	6.75	4,805@125	4,450@125	8.3	14.1	30.2	16	688	61
235/75R17.5	100EV1072Q	16	Н	143/141 J (144/144 F)	6.75	7.50	6,005@125	5,675@125	9.2	14.6	31.4	16	662	71
245/70R17.5	100EV871Q	16	Н	143/141 J (144/144 F)	7.50	6.75	6,005@127	5,675@125	9.8	14.3	31.1	17	668	70
385/65R22.5	100EV1746Q	20	L	164 K (158 L)	11.75	12.25	11,000@130	_	15.3	19.5	42.2	20	492	167

 $\textbf{PR} \ \mathsf{Ply} \ \mathsf{Rating} \qquad \textbf{LR} \ \mathsf{Load} \ \mathsf{Range} \qquad \textbf{LI} \ \mathsf{Load} \ \mathsf{Index} \qquad \textbf{SR} \ \mathsf{Speed} \ \mathsf{Rating} \qquad \textbf{RPM} \ \mathsf{Revolutions} \ \mathsf{Per} \ \mathsf{Mile}$

