







GDR652



For Trucks, Drive Position



Regional Haul Drive Tire

Features		Benefits
	Wide and deeper tread pattern	Larger tread volume for longer mileage
	Rationalized block stiffness distribution	Excellent performance in irregular wear resistance
	Open block design	Effectively prevents occurrence of "heel & toe"
	Open shoulder design	Provides good traction performance with improved heat dissipation and endurance performance

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
11R22.5	—	16	H	148/145 L	8.25	7.50	6,940@120	6,395@120	11.0	19.3	41.5	30	501	138
295/75R22.5	100EV1675Q	14	G	144/141 L	9.00	8.25	6,175@110	5,675@110	11.7	18.9	40.4	30	514	129
11R24.5	—	14	G	146/143 L	8.25	7.50	6,610@105	6,005@105	11.0	20.5	43.9	30	473	147
11R24.5	—	16	H	149/146 L	8.25	7.50	7,160@120	6,610@120	11.0	20.5	43.9	30	473	149
285/75R24.5	—	14	G	144/141 L	8.25	—	6,175@110	5,675@110	11.1	19.6	41.8	30	497	137

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Giti's new GDR652 is coming soon!

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.

