



GSR231 FS

SmartWay Verified



Regional Haul Steer Tire

Features	Benefits
 Special compound with low heat generation & longer wear	Provides higher tire mileage and improved fuel economy
 Four-straight groove design	Enhanced tread stiffness, reduce in rolling resistance, reliable control and handling
 Multiple sipes on ribs	Optimum traction & braking
 Optimized footprint distribution	Improves footprint performance to prevent irregular wear

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
295/75R22.5	100EV1674Q	14	G	144/141 L	9	8.25	6,175@110	5,675@110	11.7	18.6	39.9	21	521	123

PR Ply Rating LR Load Range LI Load Index SR Speed Rating RPM Revolutions Per Mile

Giti's new GSR231 FS is coming soon!

Product details given for information only. Giti reserves the right to modify details of products and services at any time and without notice.



The GT Radial GT279 Steer Tire is available now in additional sizes.

GT279 SmartWay Verified



Steer and trailer tire for a wide range of trucks and buses, including Light Duty all position applications.

Features	Benefits
Five straight rib pattern design	▶ Superior control and handling
Deep tread depth	▶ Long original tread life
Multiple sipes in five ribs	▶ Optimal traction and braking

SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
10R22.5	100EV477G	16	H	144/142 M	7.50	6.75	6,175@130	5,840@130	10	18.7	40.1	17.6	518	108
255/70R22.5	100EV591G	16	H	140/137 M	7.50	8.25	5,510@120	5,070@120	10.0	17.1	36.6	17	568	93
275/70R22.5	100EV627G	16	H	148/145 M	8.25	9.00	6,945@130	6,395@130	10.9	17.5	37.7	19	551	111
11R22.5	100EV794G	14	G	144/142 M	8.25	7.50	6,175@105	5,840@105	11.0	19.3	41.5	21	501	125
11R22.5	100EV611G	16	H	148/145 M	8.25	7.50	6,940@120	6,395@120	11.0	19.3	41.5	21	501	125
295/75R22.5	100EV693G	14	G	144/141 M	9.00	8.25	6,175@110	5,675@110	11.7	18.7	39.9	20	521	121
11R24.5	100EV679G	14	G	146/143 M	8.25	7.50	6,610@105	6,005@105	11.0	20.3	43.5	19	478	131
11R24.5	100EV682G	16	H	149/146 M	8.25	7.50	7,160@120	6,610@120	11.0	20.3	43.5	19	478	133
285/75R24.5	100EV761G	14	G	144/141 M	8.25	N/A	6,175@110	5,675@110	11.1	19.4	41.3	19	503	120

LIGHT DUTY SIZE RANGE

Tire Size	Item Code	PR	LR	LI/SR	Approved Wheel	Allowed Wheel	Max Load Single	Max Load Dual	Section Width	Static Loaded Radius	Overall Diameter	Tread Depth	RPM	Weight
					Inch	Inch	(Lbs. @ PSI)	(Lbs. @ PSI)	Inch	Inch	Inch	32nds		Lbs.
225/70R19.5	100EV650G	14	G	128/126 J	6.75	6.00	3,970@110	3,750@110	8.9	14.9	31.9	16	651	70
245/70R19.5	100EV662G	16	H	136/134 M	7.50	6.75	4,940@120	4,675@120	9.8	15.3	33.0	17	630	77

PR Ply Rating LR Load Range SR Speed Rating SLR Static Loaded Radius

Giti Tire Manufactures SmartWay Verified Technologies. Learn more at epa.gov/smartway.